



DEPARTMENT OF CODE ENFORCEMENT

Washington County Annex I Office Building

415 Lower Main St.

Hudson Falls, New York 12839

Phone: (518) 746-2150

Fax: (518) 746-2175

TRUSS TYPE, PRE-ENGINEERED WOOD OR TIMBER CONSTRUCTION IN RESIDENTIAL & COMMERCIAL STRUCTURES

FOR OFFICE USE ONLY APPLICATION NO. DATE RECEIVED:

Project Location: STREET / ADDRESS TOWN / VILLAGE TAX MAP SECTION BLOCK LOT

OWNER INFORMATION: NAME: MAILING ADDRESS: TELEPHONE #: E-MAIL:

PLEASE TAKE NOTICE THAT THE STRUCTURE IS (CHECK EACH APPLICABLE LINE):

- NEW STRUCTURE ADDITION TO EXISTING STRUCTURE EXISTING STRUCTURE REHABILITATION TO EXISTING STRUCTURE

TO BE CONSTRUCTED OR PERFORMED AT THE SUBJECT PROPERTY REFERENCE ABOVE WILL UTILIZE (CHECK EACH APPLICABLE LINE):

- TRUSS TYPE CONSTRUCTION (TT) PRE-ENGINEERED WOOD CONSTRUCTION (PW) TIMBER CONSTRUCTION FLOOR (TC) OTHER:

IN THE FOLLOWING LOCATION(S) (CHECK EACH APPLICABLE LINE):

- FLOOR FRAMING, INCLUDING GIRDERS AND BEAMS (F) ROOF FRAMING (R) FLOOR FRAMING AND ROOF FRAMING (FR) OTHER:

STRUCTURE CONSTRUCTION TYPE: (CHECK APPLICABLE LINE):

- TYPE I NONCOMBUSTIBLE TYPE III NONCOMBUSTIBLE EXTERIOR WALLS TYPE V (COMBUSTIBLE) OR ANY MATERIAL PERMITTED BY CODE TYPE II NONCOMBUSTIBLE TYPE IV HEAVY TIMBER

APPLICATION is hereby made to the Washington County Department of Code Enforcement for the issuance of a building permit pursuant to the provisions of Washington County Local Law No. 3 of 2007, and the Building Codes of New York State.

OWNER OR OWNER'S REPRESENTATIVE SIGNATURE DATE

IDENTIFICATION OF BUILDINGS UTILIZING TRUSS TYPE CONSTRUCTION (check appropriate symbol)

	TYPE I NONCOMBUSTIBLE	TYPE II NONCOMBUSTIBLE	TYPE III NONCOMBUSTIBLE EXTERIOR WALLS	TYPE IV HEAVY TIMBER	TYPE V ANY MATERIAL PERMITTED BY	
Floor Construction						Floor Construction
Roof Construction						Roof Construction
Floor & Roof Construction						Floor & Roof Construction

Required Sign Location(s)

Residential Construction

Affixed to electric meter box attached to the exterior of the structure or affixed to the exterior wall of the residential structure at a point immediately adjacent to the electric box or a location likely to be seen by first responders with approval by the authority having jurisdiction.

6" DIAMETER

REFLECTIVE RED PANTONE #187

REFLECTIVE WHITE

1/2" STROKE

The construction type designation shall be "I", "II", "III", "IV" or "V" to indicate the construction classification of the structure under section 602 of the BCNYS

DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS TYPE CONSTRUCTION

"F"	FLOOR FRAMING, INCLUDING GIRDERS AND BEAMS
"R"	ROOF FRAMING
"FR"	FLOOR AND ROOF FRAMING

Commercial Construction

Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached to the door, or attached to a sidelight or the face of the building, not more than 12 inches (305 mm) horizontally from the latch side of the door jamb, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached at each end of the row of doors and at a maximum horizontal distance of 12 feet (3.65M) between signs, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Fire department hose connections	Attached to the face of the building, not more than 12 inches (305 mm) horizontally from the center line of the fire department hose connection, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.

6" DIAMETER

REFLECTIVE RED PANTONE (PMS) #187

REFLECTIVE WHITE

2" MIN.

1/2" STROKE

1/4"

DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS CONSTRUCTION